



- NOTES:
1. Current Rating: 1.0A AC/DC
 2. Voltage Rating: 125V AC/DC
 3. Temperature Range: -40°C to 85°C
 4. Contact Resistance: 20mΩ Max.
 5. Insulation Resistance: 500MΩ Min.
 6. Withstanding Voltage: 250V AC/minute

- A - 125 04 H XX S - 66 - 3 - 1
- ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨
- ① A=Board to Wire Connector
 - ② 125=Pitch 1.25mm
 - ③ 04=04(Ultra-Thin) Type Series
 - ④ C=Connector/H=Housing/T=Terminal
 - ⑤ xx=No of Contacts
 - ⑥ S=Single Row Type/D=Dual Row Type
 - ⑦ PT=PB/66= Nylon 66/46= Nylon 46/
6T= Nylon 6T/9T= Nylon 9T/LP=LCP/PS=PPS
 - ⑧ 0=General(通常,一般的)/1=Without Latch/2=With Latch/
3=Without Eared/5=With Eared
 - ⑨ 1=PE Bag Packing

CX5	DMA	DM8	DMC
02	1.25	2.72	5.72
03	2.50	2.97	6.97
04	3.75	5.22	8.22
05	5.00	6.47	9.47
06	6.25	7.72	10.72
07	7.50	8.97	11.97
08	8.75	10.22	13.22
09	10.00	11.47	14.47
10	11.25	12.72	15.72
11	12.50	13.97	16.97
12	13.75	15.22	18.22
13	15.00	16.47	19.47
14	16.25	17.72	20.72
15	17.50	18.97	21.97
20	23.75	25.22	28.22
30	36.25	37.72	40.72

①	Insulator	Nylon 66/UL94V-0 / Color: Greige	1000PCS	
Specification				
Item		Parts Material	Qty	Note

① Tolerances-
Unless otherwise specified

Rev.	修正 Revisions
A.01	T1253-D14HSG Tony 2019/05/16
A.02	变更料号 Tony 2020/07/21

SRCO® 东莞市盛瑞科技有限公司
Dongguan Shengrui Technology Co., Ltd.

TEL: 86-769-8216714/87988875 MAIL: srco@dsrco.com

核准 Approved: Ian 07/21/20
審核 Checked: 郑昊 07/21/20
安規 Safety
製圖 Draw: Tong 07/21/20
頁碼 Page: 1/1

XX	: ±0.25	D: ±0.1
XXX	: ±0.13	Z: ±0.20
X	: +2°	L: ±0.90

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

Environmental standard
RHHS
Third angle projection

圖名 Description:
Pitch 1.25mm Cimp Style
Housing(Ultra-Thin)