



NOTES:

1. Current Rating: 1.0A AC/DC
2. Voltage Rating: 250V AC/DC
3. Temperature Range: -25° C to 85° C
4. Contact Resistance: 20mΩ Max.
After environmental testing: 30mΩ Max.
5. Insulation Resistance: 1000MΩ min.
6. Withstanding Voltage: 500V AC/minute
7. Applicable Wire: AWG #32 to AWG #26

A - 150 01 T 0 - P X - 3

- ① A=Board to Wire Connector
- ② 150=Pitch 1.50 mm
- ③ 01=01 (ZH) Type Series
- ④ C=Connector/H; Housing/T=Terminal
- ⑤ 0=Standard Type/M=Male Type/F=Female Type
- ⑥ B=Cross/P=Phosphor Bronze/H=High Conductivity Copper/R=Red copper
- ⑦ T=Tin Plating/G=Gold Flash Plating/N=Nickel Plating/I=Tin Matte/2=3U" Gold/3=5U" Gold/4=6U" Gold/5=10U" Gold/7=20U" Gold/8=30U" Gold/S=Silver Plating/H=Half of Gold Tin
- ⑧ 3=Tap&Reel Packing

Item	Parts Material	Specification	Qty	Note	P/N
②	Terminal	Phosphor Bronze / Gold-Plated / AWG#26-#32 / Insulation O.D. 1.10mm Max.	15,000 PCS	A15001T0-PG-3	
①	Terminal	Phosphor Bronze / Tin-Plated / AWG#26-#32 / Insulation O.D. 1.10mm Max.	15,000 PCS	A15001T0-PT-3	

Rev.		修正 Revisions	
A.01	ZH150S-H1E1P	Tony	2009/07/15
B.01	变更料号	Tony	2020/07/21

- Tolerances - Unless otherwise specified	
XX	±0.25
XX	±0.20
XXX	+0.15 / 0.20 / 0.30
XXX	+0.05 / 0.10 / 0.20
X.°	±2°

SRCO 东莞市盛瑞科技有限公司
Dongguan Shengrui Technology Co., Ltd.
TEL: 86-769-8216714/87988775 MAIL: srco@dsrco.com

機型 Model	客號 Customer P/N	盛瑞料號 Part No.	審核 Checked	審核日期 05/13/20	審核人 鄭晨
Environmental standard	A-15001T0-PX-3	RoHS	安規 Safety		
單位 Unit: mm	比例 Scale	Third angle projection	製圖 Drawn	Tong	05/13/20
			頁碼 Page	1/1	

圖名 Description: Terminal
Pitch 1.50mm (ZH) Crimp Style