



NOTES:

1. Current Rating: 1.0A AC/DC
2. Voltage Rating: 250V AC/DC
3. Temperature Range: -25° C to 85° C
4. Contact Resistance: 20mΩ Max.
- After environmental testing: 40mΩ Max.
5. Insulation Resistance: 1000MΩ min.
6. Withstanding Voltage: 500V AC/minute
7. Applicable PC Board Thickness: 0.6mm - 1.2mm.

A - 150 04 T 0 - P x - 3

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

① A=Board to Wire Connector

② 150=Pitch 1.50 mm

③ 04=04(S2N) Type Series

④ C=Connector/H: Housing/T=Terminal

⑤ 0=Standard Type/M=Male Type/F=Female Type

⑥ B=Brass/P=Phosphor Bronze/H=High Conductivity

Copper/R=Red copper

⑦ T=Tin Plating/G=Gold Flash Plating/N=Nickel Plating/I=Tin Matte/

2=3U" Gold/3=5U" Gold/4=6U" Gold/5=10U" Gold/7=20U" Gold/

8=30U" Gold/S=Silver Plating/H=Half of Gold Tin

⑧ 3=Top&Reel Packing

Item	Parts Material	Specification	Qty	Note
①	Terminal	Phosphor Bronze /half-gold-tin-plated 100-200" over Nickel-plated 30-100U" / AWG#26-#32 /Insulation O.D. 1.0mm Max.	10,000 PCS	A15004T0-PT-3 Pitch 1.50mm(S2N) Cimpo Style Terminal

**SRCO** 东莞市盛瑞科技有限公司  
Dongguan Shengrui Technology Co., Ltd.

TEL: 86-769-8216714/87988875 MAIL: srco@dsrco.com

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

修正 Revisions

Rev.	修正 Revisions	Tony 2015/07/15
A.01	MM1.50SY-TE-TP	Tony 2020/07/21
B.01	变更料号	

Unless otherwise specified

- Tolerances -

公差

公差

公差

公差

公差

公差

公差

公差

公差

公差

公差

公差

公差

公差

公差

公差

公差

公差

公差

機型 Model

-

客號 Customer P/N

-

盛瑞料號 Part No.

A-15004T0-Px-3

Environmental standard

RoHS

Specification

-

核准 Approved

07/21/20

審核 Checked

05/13/20

安規 Safety

Tong 05/13/20

圖名 Description

Terminal

頁碼 Page

1/1

單位 Unit

mm

比例 Scale

Third angle projection