



- NOTES:
1. Current Rating: 3A AC/DC
 2. Voltage Rating: 150V AC/DC
 3. Temperature Range: -25° C to 85° C
 4. Contact Resistance: 20mΩ Max.
 5. Insulation Resistance: 1000MΩ min.
 6. Withstanding Voltage: 500V AC/minute
 7. Applicable Wire: AWG #28 to AWG #24

- A - 150 06 T 0 - P x - 3
- ① A=Board to Wire Connector
 - ② 150=Pitch 1.50 mm
 - ③ 06=06(1x Ultra-thin) Type Series
 - ④ C=Connector/H; Housing/I=Terminal
 - ⑤ 0=Standard Type/M=Male Type/F=Female Type
 - ⑥ B=Brass/P=Phosphor Bronze/H=High Conductivity Copper/R=Red copper
 - ⑦ T=Tin Plating/G=Gold Flash Plating/N=Nickel Plating/I=Tin Matte/2=3U" Gold/3=5U" Gold/4=6U" Gold/5=10U" Gold/7=20U" Gold/8=30U" Gold/S=Silver Plating/H=Half of Gold Tin
 - ⑧ 3=Tap&Reel Packing

Item	Parts Material	Specification	Qty	Note	P/N
①	Terminal	Phosphor Bronze /Tin-Plated 100 - 200u" over Nickel-plated 30 - 100u" / AWG#28 - #24/ Insulation O.D. 1.10mm Max.	10,000 PCS		A15006T0-PT-3

Rev.	修正 Revisions
A.01	MX150JIN-TE-TP Tony 2015/07/15
B.01	变更料号 Tony 2020/07/21

- Tolerances - Unless otherwise specified	
公差	公差
XX : ±0.20	±0.20
XXX : ±0.15	±0.15
XXXX : ±0.05	±0.05
X° : ±2°	±2°

SRCO 东莞市盛瑞科技有限公司
Dongguan Shengrui Technology Co., Ltd.
TEL: 86-769-8216714/87988775 MAIL: srco@dsrco.com

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

机型 Model	客號 Customer P/N	盛瑞料號 Part No.	Environmental standard	單位 Unit:mm	比例 Scale	核准 Approved:ian	審核 Checked: 郑良	安規 Safety	製圖 Draw	頁碼 Page
-	-	A-15006T0-Px-3	RoHS		Third angle projection	07/21/20	05/13/20		Tong	05/13/20

圖名 Description: pitch 1.50mm(1x Ultra-thin) Crimp Style Terminal