



- NOTES:
1. Current Rating: 1.0A AC/DC
 2. Voltage Rating: 250V AC/DC
 3. Temperature Range: -25° C to 85° C
 4. Contact Resistance: 20mΩ max.
 5. Insulation Resistance: 1000MΩ min.
 6. Withstanding Voltage: 800V AC/minute
 7. Applicable Wire: AWG #28 to AWG #24

A - 200 01 H xx S - 66 - 0 - 1

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

① A=Board to Wire Connector

② 200=Pitch 2.00mm

③ 13=13(PUD) Type Series

④ C=Connector/H=Housing/T=Terminal

⑤ xx=No.of Contacts

⑥ 0=Standard/M= Male/F=female

⑦ S=Single Row Type/D=Dual Row Type

⑧ PT=PBT/66= Nylon 66/46= Nylon 46/

6T= Nylon 6T/9T= Nylon 9T/LP=LCP/PS=PPS

⑧ 0=General(通常) - 一般的/M=Male Type/F=Female Type/

S=S Type

⑨ 1=PE Bag Packing

CCS	DMA	DM8
02	2.0	4.6
03	4.0	6.6
04	6.0	8.6
05	8.0	10.6
06	10.0	12.6
07	12.0	14.6
08	14.0	16.6
09	16.0	18.6
10	18.0	20.6
11	20.0	22.6
12	22.0	24.6
13	24.0	26.6
14	26.0	28.6
15	28.0	30.6
16	30.0	32.6

修正 Revisions

Rev.	修正 Revisions	Tony	2019/05/16
A.01	A2001-nY-HM	Tony	2019/05/16
A.02	变更料号	Tony	2020/07/21

Unless otherwise specified

- Tolerances -
公差

XX	: ±0.40	±0.20	±0.15
XXX	: ±0.25	±0.20	±0.10
X	: ±0.15	±0.10	±0.05
X°	: ±2°	±1.0°	±0.5°

东莞市盛瑞科技有限公司
Dongguan Shengrui Technology Co., Ltd.

SRCO
TEL: 86-769-8216714/87988875
MAIL: srco@dsrco.com

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

Item	Parts Material	Specification	Qty	Note	P/N
①	Insulator	Nylon 66/UL94V-0	1		A20001-HHSG-201

機型 Model

各號 Customer P/N

盛瑞科技 Part No.

Environmental standard

單位 Unit:mm 比例 Scale

Third angle projection

核准 Approved:Tian 07/21/20

審核 Checked 郑斌 07/21/20

安規 Safety Tong 07/21/20

製圖 Drawn

頁碼 Page 1/1

圖名 Description:

Pitch 2.00mm Cimp Style

Housing