



- NOTES:
1. Contact Resistance: 50 milliohms Max.
  2. Insulation Resistance: 100 Mega Ohms Min.
  3. Dielectric Voltage: 500V AC one second.
  4. Operating Temperature: -25° C to 85° C

- H - 1632 01 - xx P X - R 2 - X
- ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨
- ① H=Battery Holder Connector
  - ② 1632=1632 Type
  - ③ 00=General 通常一般/01=01 type/21=21 type/F1=F1 type/31=31 type
  - ④ PT=PT/66= Nylon66/46= Nylon46/9T= Nylon9T/LP=LCP/PP=PPS
  - ⑤ C=Copper/P=Phosphor bronze/H=High conductivity copper/S=Stainless steel/M=MU Steel
  - ⑥ T=Tin plating/G=Gold flash plating/1=3U" gold/2=5U" gold/3=10U" gold/4=14U" gold/5=20U" gold/6=30U" gold/7=Nickel plating/S=Silver plating
  - ⑦ V=Vertical Dip type/R=Right Angle Dip type/L=Vertical SMT type/W=Right Angle SMT type/S=special P.C.B Module
  - ⑧ 1=Black/2=White/3=Brown
  - ⑨ 1=PE Bag Packing/2=Tube Packing/3=Tape Reel Packing/4=Hot Tape Reel Packing/5=PVC Tray Packing

Item	Parts Material	Specification	Qty	Note
③	Terminal(-)	Phosphor Bronze; ±0.15mm Sn Under-Plating(100U" - 120U")	1 PCS	163201-HTE-202
②	Terminal(+)	Phosphor Bronze; ±0.15mm Sn Under-Plating(100U" - 120U")	1 PCS	163201-HTE-201
①	Housing	LCP UL94-V0/Color:White	1 PCS	163201-HSG-101

**SRCO** 东莞市盛瑞科技有限公司  
Dongguan Shengrui Technology Co., Ltd.

Rev.	Revisions	修正/Revisions
A.01	SRBS-16AAAK006-SMT	Tony 2016/11/10
A.02	变更料号	Tony 2020/07/21

Rev.	Revisions	修正/Revisions
A.01	SRBS-16AAAK006-SMT	Tony 2016/11/10
A.02	变更料号	Tony 2020/07/21

TEL: 86-769-8216714/87988775 MAIL: srco@dsrco.com

Model	Customer P/N	Part No.	Standard	Scale	Projection	Page
163201-HTE-202	-	H163201-LPPT-R2-X	RoHS	1/1	Third angle projection	1/1

Battery CR1632-1 DIP Type