



- NOTES:
1. Contact Resistance: 30 milliohms Max.
 2. Insulation Resistance: 1000 Mega Ohms Min.
 3. Dielectric Voltage: 500V AC one second.
 4. Operating Temperature: -25° C to 85° C.

- H - 2016 01 - xx P x - L 3 - x
- ① H=Battery Holder Connector
② 2016=2016 Type
③ 00=General標準一般/01=01 type/02=02 type
④ PT=PB7/66=Nylon66/46=Nylon66/9T=Nylon9T/LP=LCP/PP=PPS
⑤ C=Copper/P=Phosphor bronze/H=High conductivity copper/S=Stainless steel/M=MU Steel/D=Multiple
⑥ T=Tin plating/G=Gold flash plating/1=3U" gold/2=5U" gold/3=10U" gold/4=14U" gold/5=20U" gold/6=30U" gold/7=Nickel plating/S=silver plating
⑦ V=Vertical Dip type/R=Right Angle Dip type/L=Vertical SWT type/W=Right Angle SWT type/S=special P.C.B Module
⑧ 1=Black/2=White/3=Brown
⑨ 1=PE Bag Packing/2=Tube Packing/3=Tape Reel Packing/4=Hot Tape Reel Packing/5=PVC Tray Packing

Item	Parts Material	Specification	Qty	Note
③	Terminal(-)	Phosphor Bronze ± 0.15 mm/ Gold Plating and Ni Under-Plating	1 PCS	162001-HTE-202
②	Terminal(+)	Phosphor Bronze ± 0.15 mm/ Gold Plating and Ni Under-Plating	1 PCS	162001-HTE-201
①	Housing	PPA / Color:Brown	1 PCS	162001-HSG-101

PCB Layout Diagram
Top View

Rev.	修正 Revisions	Tony 2016/11/10
A.01	SR65-2016-82AA001-SMT	Tony 2016/11/10
A.02	变更料号	Tony 2020/07/21

Unless otherwise specified
公差 公差 公差
XX : ±0.25 D: ±0.15
XXX : ±0.20 Z00: ±0.10
X° : ±1° L: ±0.90 ±20

东 莞 市 盛 瑞 科 技 有 限 公 司
Dongguan Shengrui Technology Co., Ltd.
TEL: 86-769-8216714/87988775 MAIL: srco@qdsrco.com

機 型 Model	客 號 Customer P/N	盛 瑞 科 號 Part No.	環 境 標 準 Environmental standard
-	-	H201601-PPA-L3-X	RoHS

核 准 Approved Tian	07/21/20	圖 名 Description:
審核 Checked	鄭 昊 07/21/20	Battery CR2016-8-1 SMT PPA
安 規 Safety		製 圖 Draw
製 圖 Draw	Tong 07/21/20	頁 碼 Page
	1/1	

Weight: 1.34g

1 2 3 4 5 6 7