



- NOTES:
1. Contact Resistance: 30 milliohms Max.
 2. Insulation Resistance: 1000 Mega Ohms
 3. Dielectric Voltage: 500V AC one second.
 4. Operating Temperature: -25° C to 85° C

- H - 2032 01 - xx P T - R 1 - x
- ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨
 - ① H=Battery Holder Connector
 - ② 2032=2032 Type
 - ③ 00=General/通常 一般/01=01 type/02=02 type/03=03 type/04=04 type
 - ④ PT=PT/66=Nylon66/46=Nylon46/9T=NYlon9T/LP=LCP/PP=PPS
 - ⑤ C=Copper/P=Phosphor bronze/H=High conductivity copper/S=Stainless steel shell/M=MU Steel
 - ⑥ T=Tin plating/G=Gold flash plating/1=3U" gold/2=5U" gold/3=10U" gold/4=14U" gold/5=20U" gold/6=30U" gold/7=Nickel plating/S=Silver plating
 - ⑦ V=Vertical Dip type/R=Right Angle Dip type/L=Vertical SWT type/W=Right Angle SWT type/S=special P.C.B Module
 - ⑧ 1=Black/2=White/3=Brown
 - ⑨ 1=PE Bag Packing/2=Tube Packing/3=Tape Reel Packing/4=Hot Tape Reel Packing/5=PVC Tray Packing

Item	Parts Material	Specification	Qty	Note
③	Terminal(-)	Phosphor Bronze; L=0.20mm Sn Plating(S100U~120U")	1 PCS	24502A-HTE-202
②	Terminal(+)	Phosphor Bronze; L=0.20mm Sn Plating(S100U~120U")	1 PCS	24502A-HTE-201
①	Housing	PA66 UL94V-0 / Color:White	1 PCS	24502A-HSG-101

Rev.	修正 Revisions
A.01	SRBS-01-A1BK002-DIP Tony 2016/11/10
A.02	变更料号 Tony 2020/07/21

- Tolerances - Unless otherwise specified	
公差	公差
XX : ±0.25	0.20~0.5
XXX : ±0.20	0.20~0.800
X : ±0.1	0.1~0.49

SRCO 东莞市盛瑞科技有限公司
Dongguan Shengrui Technology Co., Ltd.
TEL: 86-769-8216714/87988875 MAIL: srco@dsrco.com

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

機型 Model	客號 Customer P/N	盛瑞料號 Part No.	Environmental standard	單位 Unit	比例 Scale	Third angle projection
-	-	H-203201-66P-R1-x	RoHS	mm	1:1	☑

核准 Approved	日期 Date	審核 Checked	日期 Date	製圖 Drawn	日期 Date	頁碼 Page	圖名 Description
Tong	07/21/20	鄭晨	07/21/20	Tong	07/21/20	1/1	Battery CR2032-1 DIP 防呆