



- NOTES:
1. Contact Resistance: 30 milliohms Max.
 2. Insulation Resistance: 1000 Mega Ohms Min.
 3. Dielectric Voltage: 500V AC one second.
 4. Operating Temperature: -55° C to 105° C

- H - 2032 10 - xx P x - L 3 - x
- ① H=Battery Holder Connector
② 2032=2032 Type
③ 00=General(通常一般)/10=10 type
④ PT=PB/T/66=Nylon66/46=Nylon46/9T=Nylon9T/LP=LCP/PP=PPS/PA=PPA
- ⑤ C=Copper/P=Phosphor bronze/H=High conductivity copper/S=Stainless steel/M=Mn Steel
⑥ F=Tin plating/G=Gold flash plating/1=3U" gold/2=5U" gold/3=10U" gold/4=14U" gold/5=20U" gold/6=30U" gold/7=Nickel plating/S=Silver plating
⑦ V=Vertical Dip type/R=Right Angle Dip type/L=Vertical SMT type/W=Right Angle SMT type/S=special P.C.B Module
⑧ 1=Black/2=White/3=Brown
⑨ 1=PE Bag Packing/2=Tube Packing/3=Tape Reel Packing/4=Hot Tape Reel Packing/5=PVC Tray Packing

Item	Parts Material	Specification	Qty	Note
③	Terminal(-)	Phosphor Bronze, $\pm 0.20\text{mm}$ / Gold Plating (1U) and Ni Under-Plating (100U - 120U)	1 PCS	203235-HTE-202
②	Terminal(+)	Phosphor Bronze, $\pm 0.20\text{mm}$ / Gold Plating (1U) and Ni Under-Plating (100U - 120U)	1 PCS	203235-HTE-201
①	Housing	PPA / Color:Brown	1 PCS	203235-HSG-101

Rev	修正 Revisions
0A43	SRBS-10-B2A-M010-SMT Tony 2016/11/10
A02	变更料号 Tony 2020/07/21

- Tolerances - Unless otherwise specified	
XX	±0.25
XXX	±0.20
XXXX	±0.10
X.X	+0.10
X.XX	+0.05
X.XXX	+0.02
X.XXX	+0.01

SRCO 东莞市盛瑞科技有限公司
Dongguan Shengrui Technology Co., Ltd.
TEL: 86-769-8216714/6/87988775 MAIL: srco@qdsrco.com

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

機型 Model	各號 Customer P/N	盛瑞料號 Part No.	Environmental standard	單位 Unit/PM	比例 Scale	Third angle projection
-	-	H-203210-PA-Px-3-x	RoHS	☑	☑	☑

核准 Approved	Tian	日期 Date	圖名 Description
審核 Checked	鄭晨	07/21/20	Battery CR2032-10 Sony SMT
安規 Safety			
製圖 Draw	Tong	07/21/20	
頁碼 Page	1/1		