



PCB Layout Diagram
Top View

- NOTES:
1. Contact Resistance: 30 milliohms Max.
 2. Insulation Resistance: 1000 Mega Ohms Min.
 3. Dielectric Voltage: 500V AC one second.
 4. Operating Temperature: -25° C to 85° C

- H - 2032 62 - xx P X - L 2 - X
- ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨
 - 1 H= Battery Holder Connector
 - 2 2032=2032 Type
 - 3 00=General 通常一般/61=61 type/62=62 type/63=63 type/64=64 type
 - 4 PT=PBT/66=Nylon66/46=Nylon46/9T=Nylon9T/LP=LCP/PP=PPS
 - 5 C=Copper/P=Phosphor bronze/H=High conductivity copper/S=Stainless steel/M=MU Steel
 - 6 T= Tin plating/G=Gold flash plating/1=3U" gold/2=5U" gold/3=10U" gold/4=14U" gold/5=20U" gold/6=30U" gold/7=Nickel plating/S=Silver plating
 - 7 V=Vertical Dip type/R=Right Angle Dip type/L=Vertical SMT type/W=Right Angle SMT type/S=special P,C,B Module
 - 8 1=Black/2=White/3=Brown
 - 9 1=PE Bag Packing/2=Tube Packing/3=Tape Reel Packing/4=Hot Tape Reel Packing/5=PVC Tray Packing

Item	Parts Material	Specification	Qty	Note
③	Terminal(-)	Phosphor Bronze/±0.15mm/ Gold Plating(10U" -120U")	1 PCS	20325A-HTE-202
②	Terminal(+)	Phosphor Bronze/±0.15mm/ Gold Plating(10U" -120U")	1 PCS	20325A-HTE-201
①	Housing	LCP UL94-V0/Color:White	1 PCS	20325A-HSG-101

SRCO
东莞市盛瑞科技有限公司
Dongguan Shengrui Technology Co., Ltd.

TEL:86-769-8216714/87988875 MAIL:srco@dsrco.com

Rev.	修正 Revisions
A.01	SRBS-06-B4A-A002-SMT Tony 2016/11/10
A.02	变更料号 Tony 2020/07/21

公差 Tolerances	除非另有规定
XX	±0.25
XXX	±0.20/200-800 ±0.10
X	±0.15

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

機型 Model	客號 Customer P/N	盛瑞料號 Part No.	審核 Approved	日期 Date	圖名 Description
		H-203262-PPX-42-X	審核 Checked	07/21/20	Battery CR2032-6 SMT Au
Environmental standard	RoHS	Third angle projection	製圖 Drawn	Tong 07/21/20	
單位 Unit:mm	比例 Scale	頁碼 Page	1/1		