



- NOTES:
- Contact Resistance: 30 milliohms Max.
 - Insulation Resistance: 1000 Mega Ohms Min.
 - Dielectric Voltage: 500V AC one second.
 - Operating Temperature: -55° C to 105° C

- H - 2032 8C - xx P x - L 3 - x
- ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨
- H=Battery Holder Connector
 - 2032=2032 Type
 - 00=General/通常一般/8C=8C type
 - PT=PB/T/66=Nylon66/46=Nylon46/9T=Nylon9T/LP=LCP/PP=PPS/PA=PPA
 - C=Copper/P=Phosphor bronze/H=High conductivity copper/S=Stainless steel/M=Mn Steel
 - F=Ti plating/G=Gold flash plating/1=3U" gold/2=5U" gold/3=10U" gold/4=14U" gold/5=20U" gold/6=30U" gold/7=Nickel plating/S=Silver plating
 - V=Vertical Dip type/R=Right Angle Dip type/L=Vertical SMT type/W=Right Angle SMT type/S=special P.C.B Module
 - 1=Black/2=White/3=Brown
 - 1=PE Bag Packing/2=Tube Packing/3=Tape Reel Packing/4=Hot Tape Reel Packing/5=PVC Tray Packing

Item	Parts Material	Specification	Qty	Note
③	Terminal(-)	Phosphor Bronze, ±0.20mm/ Gold Plating (10U" -120U")	1 PCS	203263-HTE-202
②	Terminal(+)	Phosphor Bronze, ±0.25mm/ Gold Plating (10U" -120U")	1 PCS	203263-HTE-201
①	Housing	PPA / Color:Brown	1 PCS	203263-HSG-101

Rev	修正 Revisions
0A01	SRBS-08-82AA020-SMT Tony 2011/1/10
A02	变更料号 Tony 2020/07/21

Unless otherwise specified

- Tolerances -
公差

XXXX: ±0.20 200-800: ±0.10
XXX: ±0.20 200-800: ±0.10
XX: ±0.25 0-200: ±0.15
X: ±0.30 0-200: ±0.15

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGLU INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

TEL: 86-769-8216714/87988875 MAIL: srco@qdsrco.com

機型 Model	各號 Customer P/N	盛瑞料號 Part No.	審核 Approved	日期 Date	圖名 Description
H-20328C-3APx-3x	-	H-20328C-3APx-3x	審核 Checked	07/21/20	Battery CR2032-8GCK 0.7 SMT
單位 Unit:MM	比例 Scale	RoHS	製圖 Drawn	Tong 07/21/20	
Third angle projection	頁碼 Page	1/1			