



- NOTES:
1. Contact Resistance: 30 milliohms Max.
  2. Insulation Resistance: 1000 Mega Ohms Min.
  3. Dielectric Voltage: 500V AC one second.
  4. Operating Temperature: -55° C to 105° C

- H - 2032 8K - xx P x - L 3 - x
- ① H-Battery Holder Connector  
 ② 2032=2032 Type  
 ③ 00=General/普通/8K=8K type  
 ④ PT=PB/T/66=Nylon66/46=Nylon46/9T=Nylon9T/LP=LCP/PP=PPS/PA=PPA
- ⑤ C=Copper/P=Phosphor bronze/H=High conductivity copper/S=Stainless steel/M=Mn Steel  
 ⑥ F=Tin plating/G=Gold flash plating/1=3U" gold/2=5U" gold/3=10U" gold/4=14U" gold/5=20U" gold/6=30U" gold/7=Nickel plating/S=Silver plating  
 ⑦ V=Vertical Dip type/R=Right Angle Dip type/L=Vertical SMT type/W=Right Angle SMT type/S=special P.C.B Module  
 ⑧ 1=Black/2=White/3=Brown  
 ⑨ 1=PE Bag Packing/2=Tube Packing/3=Tape Reel Packing/4=Hot Tape Reel Packing/5=PVC Tray Packing

| Item | Parts Material | Specification                                        | Qty   | Note           |
|------|----------------|------------------------------------------------------|-------|----------------|
| ③    | Terminal(-)    | Phosphor Bronze, ±0.20mm/ Gold Plating (10U" -120U") | 1 PCS | 203285-HTE-202 |
| ②    | Terminal(+)    | Phosphor Bronze, ±0.20mm/ Gold Plating (10U" -120U") | 1 PCS | 203285-HTE-201 |
| ①    | Housing        | PPA / Color:Brown                                    | 1 PCS | 203285-HSG-101 |

| Rev  | 修正/Revisions                        |
|------|-------------------------------------|
| 0A01 | SRBS-08-B2AA002-SMT Tony 2016/11/10 |
| A02  | 变更料号 Tony 2020/07/21                |

Unless otherwise specified  
 公差: 未标注公差 标注公差  
 XX: ±0.25 0.20 ±0.5  
 XXX: ±0.20 0.20-0.80 ±0.10  
 XXXX: ±0.10 0.80-1.60 ±0.20  
 X°: ±1° L: ±0.90 ±0.20

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGJIU INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

|                                                       |                        |             |               |                       |
|-------------------------------------------------------|------------------------|-------------|---------------|-----------------------|
| 東莞市盛瑞科技有限公司<br>Dongguan Shengrui Technology Co., Ltd. | 機型 Model               | 審核/Approved | 日期/Tian       | 圖名/Description        |
| TEL: 86-769-8216714/87988775 MAIL: srco@dsrco.com     | 各號/ Customer P/N       | 審核/Checked  | 07/21/20      | Battery CR2032-8K SMT |
|                                                       | 盛瑞料號/ Part No.         | 安規/Safety   | 鄭昊 07/21/20   |                       |
|                                                       | Environmental standard | 製圖/Drawn    | Tony 07/21/20 |                       |
|                                                       | RoHS                   | 頁碼/Page     | 1/1           |                       |
|                                                       | Third angle projection |             |               |                       |