



- NOTES:
- Contact Resistance: 100 Milliohms Max.
 - Insulation Resistance: 100 Mega Ohms Min.
 - Dielectric Voltage: 500V AC one second.
 - Operating Temperature: -25° C to 85° C

- H - 2032 A1 - xx M x - R 1 - x
- ① H=Battery Holder Connector
② 2032-2032 Type
③ 00=General(標準)一般/61 type/62 type/63 type/64 type/A1 type
④ PT=PBT/66=Nylon66/46=Nylon46/9T=Nylon9T/LP=LCP/PP=PPS
⑤ C=Copper/P=Phosphor bronze/H=High conductivity copper/S=Stainless steel shell/M=MU Steel
⑥ T=Tin plating/G=Gold flash plating/1=3U" gold/2=5U" gold/3=10U" gold/4=14U" gold/5=20U" gold/6=30U" gold/7=Nickel plating/S=Silver plating
⑦ V=Vertical Dip type/R=Right Angle Dip type/L=Vertical SWT type/W=Right Angle SWT type/S=special P.C.B Module
⑧ 1=Black/2=White/3=Brown
⑨ 1=PE Bag Packing/2=Tube Packing/3=Tape Reel Packing/4=Hot Tape Reel Packing/5=PVC Tray Packing

Item	Parts Material	Specification	Qty	Note
③	Terminal(-)	Mn Steel±0.50mm/ Ni Under-Plating(100U"±120U")	1 PCS	20323A-HTE-202
②	Terminal(+)	Mn Steel±0.50mm/ Ni Under-Plating(100U"±120U")	1 PCS	20323A-HTE-201
①	Housing	PBT(U94V-0) Color:Black	1 PCS	20323A-HSG-101

PCB Layout Diagram
Top View

Rev.	修正 Revisions
A.01	SRBS-03-A1A.001-DIP Tony 2016/11/10
A.02	变更料号 Tony 2020/07/21

- Tolerances - Unless otherwise specified	
公差	公差
XX : ±0.25	±0.20
XXX : ±0.20	±0.10
X.XX : ±0.10	±0.05
X.X : ±0.05	±0.02
X : ±0.02	±0.01

SRCO 东莞市盛瑞科技有限公司
Dongguan Shengrui Technology Co., Ltd.
TEL: 86-769-8216714/6/87988775 MAIL: srco@dsrco.com

機型 Model	客號 Customer P/N	盛瑞料號 Part No.	Environmental standard	單位 Unit:mm	比例 Scale	Third angle projection	頁碼 Page
-	-	H-2032A1-PTW7-R1-X	RoHS	mm	1/1	第三角投影	1/1

核准 Approved	日期 Date	圖名 Description
審核 Checked	07/21/20	Battery CR2032-3-DIP Type
安規 Safety	07/21/20	
製圖 Draw	Tong 07/21/20	

Weight: 193g