



- NOTES:
1. Contact Resistance: 30 milliohms Max.
 2. Insulation Resistance: 1000 Mega Ohms Min.
 3. Dielectric Voltage: 500V AC one sec level.
 4. Operating Temperature: -55° C to 105° C

- H - 2032 P0 - 00 P 7 - L 0 - X
- ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨
- ① H=Battery Holder Connector
 - ② 2032=2032 Type
 - ③ 00=General(通常一般)/P0=P0 type
 - ④ PT=PB7/66=Nylon66/46=Nylon46/9T=NYlon9T/LP=LCP/PP=PP/PA=PPA/00=Without
 - ⑤ C=Copper/P=Phosphor bronze/H=High conductivity copper/S=Stainless steel/M=Mn Steel
 - ⑥ F=1in plating/G=Gold flash plating/1=3U" gold/2=5U" gold/3=10U" gold/4=14U" gold/5=20U" gold/6=30U" gold/7=Nickel plating/S=Silver plating
 - ⑦ V=Vertical Dip type/R=Right Angle Dip type/L=Vertical SMT type/W=Right Angle SMT type/S=special P.C.B Module
 - ⑧ 0=Without/1=Black/2=White/3=Brown
 - ⑨ 1=PE Bag Packing/2=Tube Packing/3=Tube Reel Packing/4=Hot Tape Reel Packing/5=PVC Tray Packing

| Item | Parts Material | Specification | Qty | Note | P/N |
|------|----------------|---|-------|--------------|----------------|
| ① | Terminal(+) | Phosphor Bronze;T=1.25mm/ Ni Under-Plating(100U"-120U") | 1 PCS | Weight:0.60g | 2032M5-HTE-201 |
| ② | | | | | |

| Rev | SRMW-2032-08-SMT | 修正 Revisions | Tony 2011/11/10 |
|-----|------------------|--------------|-----------------|
| A02 | 变更料号 | | Tony 2020/07/21 |

| -Tolerances- Unless otherwise specified 公差 | |
|--|--------------------------|
| XX | : ±0.25 |
| XXX | : ±0.20/200-800 : ±0.15 |
| XXXX | : ±0.10/800-1490 : ±0.20 |
| X.° | : ±1° |

SRCO 东莞市盛瑞科技有限公司
Dongguan Shengrui Technology Co., Ltd.
TEL: 86-769-8216714/87988875 MAIL: srco@qdsrco.com

| 機型 Model | 客號 Customer P/N | 盛瑞料號 Part No. | Environmental standard |
|----------|-----------------|--------------------|------------------------|
| - | - | H-2032P0-00P7-L0-X | RoHS |

| 核准 Approved | 日期 Date | 圖名 Description |
|-------------|---------------|-----------------------|
| 審核 Checked | 07/21/20 | Battery CR2032-P Type |
| 安規 Safety | 07/21/20 | SMT 電池扣 |
| 製圖 Draw | Tong 07/21/20 | |
| 頁碼 Page | 1/1 | |

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.