



- NOTES:
1. Contact Resistance: 30 milliohms Max.
 2. Insulation Resistance: 1000 Mega Ohms Min.
 3. Dielectric Voltage: 500V AC one sec/clevl.
 4. Operating Temperature: -55° C to 105° C

- H - 2430 01-00 P 7 - L 0 - X
- ① H=Battery Holder Connector
 - ② 2430=2430 Type
 - ③ 00=General標準一般/01=01 type
 - ④ PT=PB7/6=Nylon66/46=Nylon66/9T=Nylon9T/LP=LCP/PP=PPS/PA=PPA/00=Without
 - ⑤ C=Copper/P=Phosphor bronze/H=High conductivity copper/S=Stainless steel shell/M=Mn Steel
 - ⑥ T=1in plating/G=Gold flash plating/1=30" gold/2=50" gold/3=10U" gold/4=14U" gold/5=20U" gold/6=30U" gold/7=Nickel plating/S=Silver plating
 - ⑦ V=Vertical Dip type/R=Right Angle Dip type/L=Vertical SMT type/W=Right Angle SMT type/S=special P.C.B Module
 - ⑧ 0=Without/1=Black/2=White/3=Brown
 - ⑨ 1=PE Bag Packing/2=Tube Packing/3=Tube Reel Packing/4=Hot Tape Reel Packing/5=PVC Tray Packing

Item	Parts Material	Specification	Qty	Note	P/N
①	Terminal(+)	Phosphor Bronze(CS191),T=0.30mm/(N)Plating(100U"-120U")	1 PCS	Weight: 1.3g	243001-HTE-201
②					

Rev	修正 Revisions
0A01	SRMW-2430-01-SMT Tony 2016/11/10
A02	变更料号 Tony 2020/07/21

- Tolerances - Unless otherwise specified	
公差	公差
XX.XX : ±0.25	0.20 ~ ±0.5
XXX.XX : ±0.20	0.20 ~ ±1.0
X.XX : ±0.10	0.20 ~ ±2.0
X.X : ±0.05	0.20 ~ ±3.0

SRCO 东莞市盛瑞科技有限公司
Dongguan Shengrui Technology Co., Ltd.
TEL: 86-769-8216714/879888775 MAIL: srco@qdsrco.com

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

機型 Model	客號 Customer P/N	審核 Approved	日期 Date	圖名 Description
盛瑞料號 Part No.	H-243001-00P7-40-X	審核 Checked	07/21/20	Battery CR2430-J Type SMT
Environmental standard	RoHS	安規 Safety	Tong 07/21/20	電池扣
單位 Unit:mm	比例 Scale: 1/1	製圖 Draw	頁碼 Page 1/1	