



- NOTES:
1. Contact Resistance: 30 Milliohms Max.
  2. Insulation Resistance: 1000 Mega Ohms
  3. Dielectric Voltage: 500V AC one sec level.
  4. Operating Temperature: -25° C to 85° C

- H - 2447 02 - xx M 7 - R 1 - - x
- ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨
- ① H-Battery Holder Connector
  - ② 2447=2447 Type
  - ③ 00=General (通常) 01=01 type 02=02 type 03=03 type 04=04 type
  - ④ PT=PB7/66=Nylon66/46=Nylon66/9T=Nylon9T/LP=LC/PP=PPS
  - ⑤ C=Copper/P=Phosphor bronze/H=High conductivity copper/S=Stainless steel shell/M=Mu Steel
  - ⑥ T=Tin plating/G=Gold flash plating/1=3U" gold/2=5U" gold/3=10U" gold/4=14U" gold/5=20U" gold/6=30U" gold/7=Nickel plating/S=Silver plating
  - ⑦ V=Vertical Dip type/R=Right Angle Dip type/L=Vertical SMT type/W=Right Angle SMT type/S=Special P.C.B Module
  - ⑧ 1=Black/2=White/3=Brown
  - ⑨ 1=PE Bag Packing/2=Tube Packing/3=Tape Reel Packing/4=Hot Tape Reel Packing/5=PVC Tray Packing

Rev.	修正/Revisions	公差 - Unless otherwise specified
A.01	SRSB-24-A1A.009-DIP Tony 2016/11/10	公差: ±0.25 0.20 ±0.5
A.02	变更料号 Tony 2020/07/21	X.XXX: +0.20/0.00 -0.90: +1.0 X.: ±1° L: ±0.90: ±2.0

**SRCO** 东莞市盛瑞科技有限公司  
Dongguan Shengrui Technology Co., Ltd.

Item	Parts Material	Specification	Qty	Note
③	Terminal(-)	Mn Steel ±0.50mm / Ni(100U" - 120U") Plating	1 PCS	24472A-HTE-202
②	Terminal(+)	Mn Steel ±0.50mm / Ni(100U" - 120U") Plating	1 PCS	24472A-HTE-201
①	Housing	PBT / Color: Black	1 PCS	24472A-HSG-101

Model	Customer P/N	Part No.	Standard	Scale	Projection	Approved	Checked	Safety	Drawn	Page	Description
H-244702-PTM7-R1-X	-	-	RoHS	1/1	Third angle projection	Tian 07/21/20	郑晨 07/21/20	安规 Safety	Tong 07/21/20	1/1	Battery CR2447-2 DIP

