



- NOTES:
1. Contact Resistance: 30 milliohms Max.
 2. Insulation Resistance: 1000 Mega Ohms Min.
 3. Dielectric Voltage: 500V AC one sec/cycle.
 4. Operating Temperature: -25° C to 85° C

- H - 1220 F1 - xx P 7 - R 1 - x
- ① H=Battery Holder Connector
② 1220=1220 Type
③ 00=General/通用 一般/01=01 type/02=02 type/F1=F1 type
④ PT=PBT/66=Nylon66/46=Nylon46/9T=NYlon9T/LP=LCP/PP=PPS
⑤ C=Copper/P=Phosphor bronze/H=High conductivity copper/S=Stainless steel shell/M=MU Steel
⑥ T=Tin plating/G=Gold flash plating/1=3U" gold/2=5U" gold/3=10U" gold/4=14U" gold/5=20U" gold/6=30U" gold/7=Nickel plating/S=Silver plating
⑦ V=Vertical Dip type/R=Right Angle Dip type/L=Vertical SMT type/W=Right Angle SMT type/S=special P.C.B Module
⑧ 1=Black/2=White/3=Brown
⑨ 1=PE Bag Packing/2=Tube Packing/3=Tape Reel Packing/4=Hot Tape Reel Packing/5=PVC Tray Packing

Item	Parts Material	Specification	Qty	Note
③	Terminal(-)	Phosphor Bronze T=0.20mm/ Ni Plating(Ni 100U"=120U")	1 PCS	1220A1-HTE-202
②	Terminal(+)	Phosphor Bronze T=0.20mm/ Ni Plating(Ni 100U"=120U")	1 PCS	1220A1-HTE-201
①	Housing	PBT(U94V-0) Color:Black	1 PCS	1220A1-HSG-101

Rev.	修正 Revisions	Tony 2016/11/10
A.01	SRBS-12-A1A.002-F-DIP	Tony 2016/11/10
A.02	变更料号	Tony 2020/07/21

- Tolerances - Unless otherwise specified	
公差	公差
XX : ±0.25	±0.25
XXX : ±0.20	±0.20
XXXX : ±0.20	±0.20
X. : ±1°	±1°

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

TEL: 86-769-8216714/87988775 MAIL: srco@dsrco.com

機型 Model	客號 Customer P/N	盛瑞料號 Part No.	Environmental standard	單位 Unit:mm	比例 Scale	Third angle projection
-	-	H1220F1-PP7-R1-X	RoHS	mm	1:1	第三角投影

核准 Approved	日期 Date	圖名 Description
審核 Checked	07/21/20	Bottery CR1220-1-F 反向
安規 Safety	07/21/20	DIP Ni
製圖 Drawn	Tong 07/21/20	
頁碼 Page	1/1	