



CKTS	DMVA	DMVB	DMVC
04	6.10	1.50	2.57
05	6.60	2.00	3.07
06	7.10	2.50	3.57
07	7.60	3.00	4.07
08	8.10	3.50	4.57
09	8.60	4.00	5.07
10	9.10	4.50	5.57
11	9.60	5.00	6.07
12	10.10	5.50	6.57
13	10.60	6.00	7.07
14	11.10	6.50	7.57
15	11.60	7.00	8.07
16	12.10	7.50	8.57
17	12.60	8.00	9.07
18	13.10	8.50	9.57
19	13.60	9.00	10.07
20	14.10	9.50	10.57
21	14.60	10.00	11.07
22	15.10	10.50	11.57
23	15.60	11.00	12.07
24	16.10	11.50	12.57
25	16.60	12.00	13.07
26	17.10	12.50	13.57
27	17.60	13.00	14.07
28	18.10	13.50	14.57
29	18.60	14.00	15.07
30	19.10	14.50	15.57
31	19.60	15.00	16.07
32	20.10	15.50	16.57
33	20.60	16.00	17.07
34	21.10	16.50	17.57
35	21.60	17.00	18.07
36	22.10	17.50	18.57
37	22.60	18.00	19.07
38	23.10	18.50	19.57
39	23.60	19.00	20.07
40	24.10	19.50	20.57
41	24.60	20.00	21.07
42	25.10	20.50	21.57
43	25.60	21.00	22.07
44	26.10	21.50	22.57
45	26.60	22.00	23.07
46	27.10	22.50	23.57
47	27.60	23.00	24.07
48	28.10	23.50	24.57
49	28.60	24.00	25.07
50	29.10	24.50	25.57
51	29.60	25.00	26.07
52	30.10	25.50	26.57
53	30.60	26.00	27.07
54	31.10	26.50	27.57
55	31.60	27.00	28.07
56	32.10	27.50	28.57
57	32.60	28.00	29.07
58	33.10	28.50	29.57
59	33.60	29.00	30.07
60	34.10	29.50	30.57



Rev.	修正 Revisions	Unless otherwise specified
A.01	SR-0515-xxCl-SN-1B Tony 2019/05/16	
A.02	变更料号 Tony 2020/07/21	

Item	Parts Material	Specification	Qty	Note
④	Fitting Nail	Boss: I=0.20mm / Tin over nickel	2 PCS	A050AZ-TS4B-202
③	Terminal	Phosphor Bronze I=0.15mm / Tin over nickel	CKTS PCS	A050AZ-TTEG-201
②	Latch	LCPJU94-V0/Color: Black	1 PCS	A123AZ-CLAT-102
①	Housing	LCPJU94-V0/Color: Nature	1 PCS	A050AZ-CHSG-101

Model	各款 Customer P/N	核准 Approved Tian	07/21/20	圖名 Description:
盛瑞科技 Part No.	F-050Gx6-LPPT-W42-x	審核 Checked 郑斌	07/21/20	ZIF FOR FFC/FPC PH
Environmental standard	RoHS	製圖 Drawn Tong	07/21/20	0.50mm ASSY
單位 Unit:mm	比例 Scale	頁碼 Page	1/1	

東莞市盛瑞科技有限公司
Dongguan Shengrui Technology Co., Ltd.
TEL: 86-769-8216714/87988775 MAIL: srco@dsrco.com

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGUO INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

容許公差 封裝公差 公差
XX: ±0.25 0.20 ±0.5
XXX: ±0.20 0.20 ±0.5
X: ±5° L: ±0.90 ±0.20

1. Current Rating: 0.4A AC/DC
2. Voltage Rating: 50V AC/DC
3. Temperature Range: -20°C to 85°C
4. Contact Resistance: 20mΩ Max.
5. After Environmental testing: 20mΩ Max.
6. Insulation Resistance: 500MΩ min.

F - 050 G xx B - LP P T - W 4 Z - X
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪ ⑫
① F=FFC/FPC Connector
② 050=Pitch 0.50mm
③ A=A Type Series
④ XX= No of Contacts
⑤ B=Bottom Contact Type/I=Top Contact Type/R=Vertical Right Contact Type/V=Vertical Left Contact Type/S=Single Contact Type/D=Dual Contact/N=Indiscriminate
⑥ PT=PT/66= NYLON 66/46= NYLON 46/6T= NYLON 6T/9T= NYLON 9T/LP=LCP/PP=PPS
⑦ B=Brass/P=Phosphor Bronze/H=High conductivity copper/R=Red copper/C=Copper Alloy
⑧ Surface Processing: 0=None/I=In Bright/G=Gold Flash Plating/N=Nickel Plating/I=In Matte/2=3u" Gold/3=5u" Gold/4=6u" Gold/5=10u" Gold/6=15u" Gold/7=20u" Gold/8=30u" Gold/9=Silver Plating/H=Half of Gold Tin
⑨ V=Vertical Dip type/R=Right Angle Dip type/L=Vertical SMT type/W=Right Angle SMT Type/S=Special P.C.B Mode
⑩ Insulator Height: 1=0.90mm/2=1.00mm/3=1.20mm/4=1.50mm/5=2.00mm/6=2.70mm/7=3.00mm/8=5.00mm/N=Indiscriminate
⑪ N=Non-ZIF Type/L=ZIF Type
⑫ Packaging: 1=PE bag/2=tube/3=Reel/4=Hot Tape&Reel/5=Reel+CAP/6=Reel+MWor/7=PC Tray/8=tube+CAP/9=tube+MWor

Notes:
1. Current Rating: 0.4A AC/DC
2. Voltage Rating: 50V AC/DC
3. Temperature Range: -20°C to 85°C
4. Contact Resistance: 20mΩ Max.
5. After Environmental testing: 20mΩ Max.
6. Insulation Resistance: 500MΩ min.

F - 050 G xx B - LP P T - W 4 Z - X
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪ ⑫
① F=FFC/FPC Connector
② 050=Pitch 0.50mm
③ A=A Type Series
④ XX= No of Contacts
⑤ B=Bottom Contact Type/I=Top Contact Type/R=Vertical Right Contact Type/V=Vertical Left Contact Type/S=Single Contact Type/D=Dual Contact/N=Indiscriminate
⑥ PT=PT/66= NYLON 66/46= NYLON 46/6T= NYLON 6T/9T= NYLON 9T/LP=LCP/PP=PPS
⑦ B=Brass/P=Phosphor Bronze/H=High conductivity copper/R=Red copper/C=Copper Alloy
⑧ Surface Processing: 0=None/I=In Bright/G=Gold Flash Plating/N=Nickel Plating/I=In Matte/2=3u" Gold/3=5u" Gold/4=6u" Gold/5=10u" Gold/6=15u" Gold/7=20u" Gold/8=30u" Gold/9=Silver Plating/H=Half of Gold Tin
⑨ V=Vertical Dip type/R=Right Angle Dip type/L=Vertical SMT type/W=Right Angle SMT Type/S=Special P.C.B Mode
⑩ Insulator Height: 1=0.90mm/2=1.00mm/3=1.20mm/4=1.50mm/5=2.00mm/6=2.70mm/7=3.00mm/8=5.00mm/N=Indiscriminate
⑪ N=Non-ZIF Type/L=ZIF Type
⑫ Packaging: 1=PE bag/2=tube/3=Reel/4=Hot Tape&Reel/5=Reel+CAP/6=Reel+MWor/7=PC Tray/8=tube+CAP/9=tube+MWor