



注解:  
1. \*为重点尺寸

Item	Parts Material	Specification	Qty	Note	P/N
①	Insulator Nylon 66/ Color: White		✕	A25001-H665-201	

Rev.	修正 Revisions	Tony
A.01	2512-NY	2009/07/15
B.01	变更料号	2020/07/21

Unless otherwise specified  
公差  
规格公差 制程公差  
XX: ±0.30 D: 200 ±.15  
XXX: ±0.20 Z00: 800 ±.10  
X.X: ±.2° L: ±4.90 ±.30

**SRCO** 东莞市盛瑞科技有限公司  
Dongguan Shengrui Technology Co., Ltd.  
TEL: 86-769-8216714/6/87988775 MAIL: srco@qdsrco.com

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

機型 Model	各號 Customer P/N	盛瑞料號 Part No.	環境標準 Environmental standard	單位 Unit:mm	比例 Scale	第三角投影 Third angle projection	頁碼 Page
-	-	A-25012H04S-66-0-1	ROHS	mm	1:1	☉	1/1

- NOTES:
1. Current Rating: 3.0A AC/DC
  2. Voltage Rating: 250V AC/DC
  3. Temperature Range: -25° C to 85° C
  4. Contact Resistance: 10mΩ Max.  
After environmental testing: 30mΩ Max.
  5. Insulation Resistance: 1000MΩ min.
  6. Withstanding Voltage: 1000V AC/minute
  7. Applicable Wire: AWG #28 to AWG #22
- A - 250 12 H xx S - 66 - 8 - 1
- ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨
- ① A=Board to Wire Connector
  - ② 250=Pitch 2.50mm
  - ③ 12=12(For Led Model) Type Series
  - ④ C=Connector/H=Housing/T=Terminal
  - ⑤ XX=No.of Contacts
  - ⑥ S=Standard/M= Male/F=Female
  - ⑦ PT=Single Row Type/D=Dual Row Type
  - ⑧ 6T= Nylon 6T/9T= Nylon 9T/1P=LCP/PS=PPS/FR= Dupont FR50
  - ⑨ 1=PE Bag Packing
- ⑧ 1=For 1.3 Standard/2=For 1.0 Standard/5=錯位的/8= 1.3短靠背/9=1.0短靠背/M=Male type/F=Female Type

E

D

C

B

A

E

D

C

B

A