



NOTES:

1. Current Rating: 1.0A AC/DC
 2. Withstand Voltage: 100V AC/minute
 3. Working Temperature: -40° C to 105° C
 4. Insulation Resistance: 500MΩ Min.
 5. Contact Resistance: 30mΩ Max.
- P - 200 3 S 02 K 1 - PT B G - 0 101 B - 1
- ① ②③④ ⑤⑥⑦ ⑧ ⑨⑩ ⑪⑫⑬ ⑭
- ① P=PIN/Female Header series
 ② 2.00=Pitch 2.00mm
 ③ 1=Pin header/2=Female header/ 3=Mini Jumper/ 4=Machined Pin header/ 5=Machined Female Header/M=M Type
 ④ S=Single Row/D= Double Row/T=Three Row/F=Four Row
 ⑤ XX=No. of Contacts
 ⑥ Insulator Height: A=1.0mm/B=1.35mm/C=1.5mm/D=1.70mm/E=1.95mm/
 F=2.0mm/G=2.5mm/H=3.0mm/I=3.2mm/J=3.4mm/K=3.5mm/L=4.0mm/M=4.3mm/
 N=4.6mm/O=5.0mm/P=5.7mm/Q=6.0mm/R=6.35mm/S=7.0mm/T=7.1mm/
 U=7.2mm/V=8.1mm/W=8.5mm/X=8.9mm/Y=4.50mm/Z=4.50mm/0=Indiscriminate/Y=2.54mm
 /1=7.40mm/2=3.10mm/4=4.50mm/5=2.10mm
 ⑦ Insulator Quantity: 1=1 Insulator/ 2=2 Insulator/ 3=3 Insulator
 ⑧ PBT/66= Nylon 66/46= Nylon 46/6T= Nylon 6T/9T= Nylon 9T/LP= LCP/PS= PS
 ⑨ C=Copper Alloy/B=Brass/P=Phosphor Bronze/H=High conductivity copper/R=Red Copper
 ⑩ Plating/0=None/1=In Bright/N=Nickel Plating/G=Gold Flash Plating/I=Tin Matte/2=3U" Gold/3=5U" Gold/4=10U" Gold/5=15U" Gold/6=20U" Gold/7=15U" Gold/8=30U" Gold/9=Silver Plating/H=Half of Gold Tin
 ⑪ V=Vertical Dip Type/R=Right Angle Dip Type/L=Vertical SMT Type/W=Right Angle SMT Type/S=Special PCB Model/O=Without
 ⑫ 101=Product Identification Code
 ⑬ Color: B=Black/W=White/R=Red/U=Blue/G=Green/E=Gray
 ⑭ Packaging: 1=PE bag/2=Tube/3=Reel/4=Hot Tape Reel/5=Reel/6=Reel/CAP/ 6=Tube&Reel/PEI/=PVC Tray/8=Tube+CAP/9=Tube+PEI

Item	Parts Material	Specification	Qty	Note	P/N
②	Contact	Brass/Plating: Au over Ni	×		P200T-050-10GF
①	Insulator	PBT+30%GF UL 94V-0	×		P2004-450-6T01

SRCO 东莞市盛瑞科技有限公司
 Dongguan Shengrui Technology Co., Ltd.

TEL: 86-769-8216714/87988875 MAIL: srco@qdsrco.com
 THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

修正 Revisions

Rev.	变更科号	变更日期
A.01	新增规格	Tony 2013/07/15
B.01	变更科号	Tony 2020/12/09

Unless otherwise specified

公差	公差	公差
XX : +0.35 0-200 : +0.5	公差	公差
XXX : +0.30 200-800 : +1.0	公差	公差
公差	公差	公差

機型 Model

各號 Customer P/N	盛瑞科號 Part No.	環境標準 Environmental standard	單位 Unit/mm	比例 Scale	第三角投影 Third angle projection	核准 Approved Tian	日期 Date	圖名 Description
-	P-2003S02K1-PTB-G-010-B-1	RoHS	mm	1:1	第三角投影	12/09/20	12/09/20	2.00mm MINI Jumper H=3.50mm Open Type Connector
審核 Checked	安規 Safety	製圖 Drawn	設計 Design	日期 Date	日期 Date			