



NOTES:

- Current Rating: 3.0A AC/DC
 - Withstand Voltage: 250V AC/minute
 - Working Temperature: -40° C to 105° C
 - Insulation Resistance: 500MΩ Min.
 - Contact Resistance: 20mΩ Max.
- P - 254 3 S 02 7 1 - PT B G - 0 301 B - 1
- ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪ ⑫ ⑬ ⑭
 - P=PIN/Female Header series
 - 2.54=Pitch 2.54mm
 - I=Pin header/2=Female header/3=Mini Jumper/4=Machined Pin header/5=Machined Female Header/M=M Type
 - S=Single Row/D= Double Row/T=Three Row/F=Four Row
 - XX=No. of Contacts
 - Insulator Height: A=1.0mm/B=1.35mm/C=1.5mm/D=1.70mm/E=1.95mm/F=2.0mm/G=2.5mm/H=3.0mm/I=3.2mm/J=3.4mm/K=3.5mm/L=4.0mm/M=4.3mm/N=4.6mm/O=5.0mm/P=5.7mm/Q=6.0mm/R=6.35mm/S=7.0mm/T=7.1mm/U=7.2mm/V=8.1mm/W=8.5mm/X=8.9mm/Y=4.50mm/Z=4.50mm/0=Indiscriminate/V=2.54mm/1=7.40mm/2=3.10mm/4=4.50mm/5=2.10mm/6=6.50mm/7=3.50mm
 - Insulator Quantity: 1=1 Insulator/2=2 Insulator/3=3 Insulator
 - PT1/66= Nylon 66/46= Nylon 46/67= Nylon 67/97= Nylon 97/LP= LCP/PS= PS
 - C=Copper Alloy/B=Brass/P=Phosphor Bronze/H=High conductivity copper/R=Red Copper
 - Plating: 0=none/1=Tin Bright/N=Nickel Plating/G=Gold Flash Plating/I=Tin Mottle/2=3U" Gold/3=5U" Gold/4=10U" Gold/5=15U" Gold/6=20U" Gold/7=15U" Gold/8=30U" Gold/9=Silver Plating/H=Half of Gold Tin
 - Package: 1=PE bag/2=tube/3=Reel/4=lot Tape Reel/5=tape&Reel/CAP/6=tape&Reel+PEI/7=PVC Tray/8=tube+CAP/9=tube+PEI
 - V=Vertical Dip Type/R=Right Angle Dip Type/L=Vertical SMT Type/W=Right Angle SMT Type/S=Special PCB Model/O=without
 - 301=Product Identification Code
 - Color: B=Black/W=White/R=Red/U=Blue/G=Green/E=Gray

Item	Parts Material	Specification	Qty	Note	P/N
②	Contact	Bross/Plating: Au over Ni	×		P254T-001-10GF
①	Insulator	PBT+30%GF UL 94V-0	×		P2543-135-PT01

SRCO 东莞市盛瑞科技有限公司
Dongguan Shengrui Technology Co., Ltd.

TEL: 86-769-8216714/87988775 MAIL: srco@dsrco.com

修正 Revisions

Rev.	修正 Revisions
A.01	新增规格 Tony 2013/07/15
B.01	变更料号 Tony 2020/12/09

Unless otherwise specified

- Tolerances -

公差

连续公差 连续公差

XX : ±0.30 D=200 ~ ±0.5

XXX : ±0.20 200-800 ±0.10

XXXX : ±0.20 800-490 ±0.20

Page: 1/1 L : +4.90 ±0.10

机型 Model

客规 Customer P/N

盛瑞料号 Part No.

Environmental standard

单位 Unit:mm

比例 Scale

批准 Approved:Jan 12/09/20

审核 Checked

安规 Safety

製圖 Draw

設計 Design

Tong 12/09/20

圖名 Description: 2.54mm MINI Jumper H=3.50mm Close Type Connector

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.