


TYPE 2(1D) WITH POST



TYPE 2(1D0) WITH POST

NOTES:

1. Current Rating: 2A AC,DC
2. Withstand Voltage: 500V AC/minute
3. Working Temperature: -40° C to 105° C
4. Insulation Resistance: 1000MΩ Min.
5. Contact Resistance: 20mΩ Max.

P - 200 1 D xx F 1 - xx B G - S XDX B - 1  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪ ⑫ ⑬ ⑭

- ① P=PIN/Female Header series
- ② 200=Pitch 2.00mm
- ③ 1=Pin header/2=Female header/3=Mini Jumper/4=Machined Pin header/5=Machined Female Header/M=W Type
- ④ S=Single Row/D= Double Row/T=Three Row/F=Four Row
- ⑤ XX=No. of Contacts
- ⑥ Insulator Height: A=1.0mm/β=1.35mm/C=1.5mm/D=1.70mm/E=1.95mm/F=2.0mm/G=2.5mm/H=3.0mm/I=3.2mm/J=3.4mm/K=3.5mm/L=4.0mm/M=4.3mm/N=4.6mm/O=5.0mm/P=5.7mm/Q=6.0mm/R=6.35mm/S=7.0mm/T=7.1mm/U=7.2mm/V=8.1mm/W=8.5mm/X=8.9mm/Y=9.4mm/Z=4.50mm/θ=Indicimangle/Y=2.54mm
- ⑦ Insulator Quantity: 1=1 Insulator/2=2 Insulator/3=3 Insulator
- ⑧ PBT/66= Nylon 66/46= Nylon 46/6T= Nylon 6T/9T= Nylon 9T /I.P.: LCP/PS= PPS
- ⑨ C=Copper Alloy/β=Brass/P=Phosphor Bronze/H=High conductivity copper/R=Red Copper
- ⑩ Plating: 0=None/I=In Bright/N=Nickel Plating/G=Gold Flash Plating/I=Tin Matte/2=3U" Gold/3=5U" Gold/4=10U" Gold/5=15U" Gold/6=20U" Gold/7=15U" Gold/8=30U" Gold/9=Silver Plating/H=Half of Gold Tin
- ⑪ X=V= Vertical Dip Type/R= Right Angle Dip Type/L=Vertical SMT Type/ W=Right Angle SMT Type/S=Special P.C.B Model
- ⑫ IT0=Product Identification Code
- ⑬ Color: B=Black/W=White/R=Red/U=Blue/G=Green/E=Grey
- ⑭ Packaging: 1=PE bag/2=tube/3=Reel/4=lot Tape Reel/5=tape&Reel/CAP/ f=tape&Reel/HFI/=PVC Tray/8=tube+CAP/9=tube+PEI

Item	Product Identification Code	Pin Length	A	D	W	C
Standard	XDX	-	4.00	0.10	6.50	-
Alternate						

Item	Parts Material	Specification	Qty	Note	P/N
②	Contact	Brass/Gold flash all over nickel	×		P200T-050-10GF
①	Insulator	PA6T+30%GF & PA9T+30%GF,UL 94V-0	×		P2004-020-6T01

Rev.	修正 Revisions	修正 Revisions	修正 Revisions
A.01	新增规格	Tony 2021/12/09	
<p>SRCO 东莞市盛瑞科技有限公司          Dongguan Shengrui Technology Co., Ltd.          TEL: 86-769-8216714/87988775 MAIL: srco@dsrco.com</p>			
<p>THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.</p>			
Model	各款 Customer P/N	盛瑞科技 Part No.	RoHS
Environmental standard	P-2001 DxxF 1-xx8 S-SDx8-1	RoHS	Third angle projection
Unit: mm	比例 Scale	设计 Design	Tong 12/09/21
核准 Approved	Tian 12/09/21	审核 Checked	
安规 Safety	12/09/21	製圖 Drawn	郑斌 12/09/21
圖名 Description:	PH2.00mm 2xpinx2 Vertical SMT to Right Angle Type Pin Header		