



接线表 (WIRING TABLE)

P1	P2	Twisted (16)
1	1	
2	2	2 and 4 (65)
3	3	twisted pairs
4	4	twisted pairs
5	5	6 and 8 (65)
6	6	twisted pairs
7	7	twisted pairs
8	8	
9	9	
10	10	
11	11	
12	12	12 and 14 (65)
13	13	twisted pairs
14	14	twisted pairs
15	15	
16	16	
17	17	
18	18	
19	19	18 and 20 (65)
20	20	twisted pairs

Wire Model	AWG	Color	Quantity	Cutting Length	P1 Peeling length	P2 Peeling length
UL10064	32 AWG	Yellow	6	225±1	1.5±0.1	1.5±0.1
UL10064	32 AWG	Brown	6	225±1	1.5±0.1	1.5±0.1
UL10064	32 AWG	Yellow	4	235±1	1.5±0.1	1.5±0.1
UL10064	32 AWG	Brown	4	235±1	1.5±0.1	1.5±0.1

Terminal model	AWG	Crimping height/Crimping Width	Insulation Diameter	Ingruption Width	Temple Strength	Retention force
SH1.0-1-T	32 AWG	0.55±0.05	0.75±0.05	0.60±0.05	0.7 kgf	0.4 kgf

- ✓ Electrical performance
- Open/Short/Intermittence 100% Test.
 - Conductor Resistance: 1Ω Max.
 - Insulation Resistance: DC 200V 20MΩ Min.

- ✓ 注意事项:
- *Means important control dimensions:
 - PIN2/PIN4 twisted pairs, PIN14/PIN16 twisted pairs, P1 end acetate cloth L=20mm;
 - Twisted pair direction is unified in a clockwise direction;

ITEM	TITLE	SPECIFICATION	QTY	P/N
④	Glue	UV Glue	1.5g	
③	HSG	Pitch 1.0mm*2*10pin Housing PA66	2PCS	
②	TER	Pitch 1.0mm SH1.0T-1-T	40PCS	
①	Wire	UL10064#32AWG(19/0.05TS+200D)防弹丝, OD:0.48mm) INSULATION: 铁氟龙	20PCS	

Rev.	修正 Revisions	- Tolerances - Unless otherwise specified 公差		东莞市盛瑞科技有限公司 Dongguan Shengrui Technology Co., Ltd.	机型 Model	-	核准 Approved	日期 Date	图名 Description
		XX : ±	XX ^o : ±	TEL: 86-769-8216714/87988875	客模 Customer P/N	-	審核 Checked	02/21/20 ^o	1.0mm*2*10pin to Wire
		XXX : ±	XXX ^o : ±	MAIL: srco@dsrco.com	盛瑞料號 Part No.	W-1006432-B-1031-1	安規 Safety	02/21/20 ^o	Harness
		XXXX : ±	XXXX ^o : ±	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SHENGRUI INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	Environmental standard	RoHS	製圖 Draw	郑斌	
		公差 Tolerance	公差 Tolerance		單位 Unit/mm	比例 Scale	設計 Design	Tony	